



EtherHaul™-1200 - Gigabit Ethernet Wireless Solution

Introducing EtherHaul™-1200

The EtherHaul-1200 is Siklu's next generation, millimeter-wave, all-outdoor, Ethernet backhaul product. The EtherHaul-1200 features up to 1 Gbps Ethernet, carrier grade networking capabilities, operating at the 71-76 GHz licensed E-Band with enhanced Adaptive Bandwidth, Coding & Modulation capabilities for maximum spectral efficiency. Designed with strenuous carrier wireless backhaul demands in mind, the EtherHaul-1200 is equally at home in the mobile backhaul, in the enterprise or in Ethernet service provider networks.

Radio Specifications

Standards	ETSI, FCC
Operating Frequency Range	71-76 GHz
Air Interface	TDD, OFDM
Channel Size	500 MHz, 250 MHz
RF Channel Arrangement	500 MHz: $71375 + n \times 500$ MHz, $n=0\dots8$ 250 MHz: $71250 + n \times 250$ MHz, $n=0\dots18$
RF Channel Selection	Via EMS/NMS/CLI
Transmit Power (typical)	+5 dBm
Adaptive Bandwidth, Coding and Modulation Dynamic Range	21 dB
Typical link distance ⁽¹⁾	Up to 2,500 m. (8,200 ft.)

Notes:

(1) Max. 4,500 m. (max. 14,765 ft.)

Antenna

Type	Integrated, Cassegrain reflector	Integrated, Cassegrain reflector	External, Cassegrain reflector (EH-ANT-2ft)
Diameter	26 cm (10.3")	31 cm (12.2")	65 cm (25.6")
Gain (dBi)	42	45	50
3 dB Beam width	1°	0.8°	0.5°
Radiation Pattern Envelope	Class 2 (ETSI EN 302 217-4-2 V1.5.1)	Class 2, Class 3 (ETSI EN 302 217-4-2 V1.5.1) FCC 47CFR101.115	Class 2, Class 3 (ETSI EN 302 217-4-2 V1.5.1) FCC 47CFR101.115

Capacity

250 MHz Channel Mode

Mode	Bandwidth (MHz)	Modulation	FEC Rate	Repetitions	L1 Rate (Mbps) ^(1,2)	
					Maximum	Minimum
0	250	QAM 64	0.5	1	514	477
1	250	QAM 16	0.5	1	349	321
2	250	QPSK	0.5	1	182	160
3	125	QPSK	0.5	2	42	39
4	62.5	QPSK	0.5	4	10	9

Notes:

- (1) Aggregated capacity. Capacity may be divided at a ratio of: 50%-50% downstream-upstream, 75%-25% downstream-upstream or 90%-10% downstream-upstream.
- (2) Capacity increases when divided asymmetrically (75%-25%, 90%-10%).
- (3) Capacity varies according to packet size.

500 MHz Channel Mode

Mode	Bandwidth (MHz)	Modulation	FEC Rate	Repetitions	L1 Rate (Mbps) ^(1,2)	
					Maximum	Minimum
0	500	QAM 64	0.5	1	1028	955
1	500	QAM 16	0.5	1	699	642
2	500	QPSK	0.5	1	365	320
3	250	QPSK	0.5	2	85	79
4	125	QPSK	0.5	4	20	19

Notes:

- (1) Aggregated capacity. Capacity may be divided at a ratio of: 50%-50% downstream-upstream, 75%-25% downstream-upstream or 90%-10% downstream-upstream.
- (2) Capacity increases when divided asymmetrically (75%-25%, 90%-10%).
- (3) Capacity varies according to packet size.

Receiver Threshold (dBm @ BER = 10⁻⁶)

250 MHz Channel Mode

Mode	Bandwidth (MHz)	Modulation	FEC Rate	Repetitions	Pout (dBm)	Receiver Threshold (dBm @ BER=10 ⁻⁶)
0	250	QAM 64	0.5	1	+6	-62
1	250	QAM 16	0.5	1	+6	-67
2	250	QPSK	0.5	1	+7	-72
3	125	QPSK	0.5	2	+8	-76
4	62.5	QPSK	0.5	4	+8	-79

Note: Receiver threshold levels are typical

500 MHz Channel Mode

Mode	Bandwidth (MHz)	Modulation	FEC Rate	Repetitions	Pout (dBm)	Receiver Threshold (dBm @ BER=10 ⁻⁶)
0	500	QAM 64	0.5	1	+5	-59
1	500	QAM 16	0.5	1	+5	-64
2	500	QPSK	0.5	1	+6	-69
3	250	QPSK	0.5	2	+7	-73
4	125	QPSK	0.5	4	+8	-77

Note: Receiver threshold levels are typical

Ethernet Interfaces

Supported Ethernet Interfaces	2 x 100/1000Base-T (RJ45) 2 x 1000Base-X (SFP)
Supported SFP Types	1000Base-LX (1310 nm), SX (850 nm)

Carrier Ethernet Functionality

Latency over the radio link (typical) ⁽¹⁾	350 µsec @ highest mode of operation
Jumbo frames support	Up to 9,200 Bytes
Carrier Ethernet Switch	4096 active VLANs MAC address learning with 4K MAC addresses IEEE 802.1ad Provider Bridge (QinQ) IEEE 802.1d Transparent Bridging IEEE 802.1ag Ethernet Service OAM (CFM) ITU-T Y.1731 OAM functions and mechanisms for Ethernet based networks IEEE 802.3ah Ethernet Link OAM (EFM) ITU-T G. 8032 Ethernet Ring Protection ITU-T G. 8031 Ethernet Linear Protection IEEE 802.1ad Link Aggregation Link state propagation
Quality of Service	Advanced CoS classification and prioritization Per interface CoS based packet queuing / buffering (8 CoS served by 8 queues) Flexible scheduling schemes (SP/WFQ/Hybrid) Traffic shaping Traffic policing
Synchronization	G.8262, G.8264 Synchronous Ethernet IEEE 1588v.2 Timing-over-packet optimized transport
Performance Monitoring	Per Ethernet port statistics Per VLAN statistics Per queue statistics Enhanced radio Ethernet statistics
Encryption	AES 128, AES 256

Notes:

(1) Latency varies according to packet size and load

Network Management, Diagnostics, Status and Alarms

Network Management System	SikluView NMS
NMS Interface Protocol	SNMP v1/v2/v3
Element Management	Web-based EMS, CLI,
Management Channels & Protocols	SSH HTTPS
Authentication, Authorization & Accounting	User access control SYSLOG
Management Interface	Via the Ethernet interfaces
RSSI Indication	Accurate power reading available at ODU and EMS

Mechanical

Form Factor	All-outdoor
Dimensions ODU (H x W x D): Antenna - 26 cm, 10.3" (Dia. x Depth): Antenna - 31 cm, 12.2" (Dia. x Depth): Antenna - 65 cm, 25.6" (Dia. x Depth):	24.5 cm x 22.5 cm x 5 cm (9.7" x 8.9" x 2") 26 cm x 10 cm (10.3" x 3.9") 31 cm x 11 cm (12.2" x 4.3") 65 cm x 37 cm (25.6" x 14.6")
Weights ODU+ antenna (26 cm, 10.3"): ODU+ antenna (31 cm, 12.2"): ODU: Antenna (26 cm, 10.3"): Antenna (31 cm, 12.2"): Antenna (65 cm, 25.6"):	3 kg (6.6 lbs) 3.5 kg (7.7 lbs) 2 kg (4.4 lbs) 1 kg (2.2 lbs) 1.5 kg (3.3 lbs) 8 kg (18 lbs)
Mounting kit	EH-MK-1ft (26 / 31 cm antenna) EH-MK-2ft (EH-ANT-2ft)

Environmental

Operating Temperature (°C)	-45° ÷ +55°C (-49° ÷ +131°F)
Relative Humidity	0 to 100%
Ingress Protection Rating	IP67
Altitude	4,500 m. (14,765 ft.)

Power Input and Consumption

Standard Input	±48 VDC, ±24 VDC
DC Input Range	±21 ÷ ±57 VDC
Power over Ethernet Input	IEEE 802.3at-2009
Power Consumption (typical)	25W

Standard Compliance

CE	CE Marked
RF	EN 302 217-3 1.3.1 FCC 47 CFR part 101:2009
EMC	EN 301 489-4 FCC 47 CFR part 15
Safety	UL 60950
Operation	EN 300 019-1-4 Class 4.1E
Storage	EN 300 019-1-1 Class 1.2
Transportation	EN 300 019-1-2 Class 2.2

About Siklu

Siklu redefines wireless backhaul by optimizing every aspect of mm-wave system design to enable service providers to boost network capacity and performance, while dramatically reducing costs by 80%. By re-engineering mm-wave system components, and leveraging silicon-based technologies, Siklu provides gigabit-per-second wireless connectivity at the lowest price point in the industry. Siklu's solutions are easily scalable enabling service providers to evolve their networks from 2G/3G to HSPA and 4G and incorporate capabilities to support future topologies. In addition, Siklu's environmentally friendly design results in easier and quicker deployment and adoption.

Siklu Communication Ltd.
7, Shoham St.
Petach Tikva 49517, Israel
Tel: +972 3 921 4015
Fax: +972 3 921 4162
info@siklu.com

The Siklu logo and EtherHaul™ are trademarks of Siklu Communication Ltd. This brochure is for information purposes only. The details contained in this document, including product and feature specifications, are subject to change without notice. This brochure shall not bind Siklu to provide to anyone a specific product or set of features related thereto.



www.siklu.com